

AQUASYSTEM

watertech



Duzone systems Co., Ltd.

키워드 : 더존펌프

SERIES VAO

VAO



Pressure tank with replaceable membrane for pressurized systems of sanitary water.

Working temperature
- 10° C
+ 100° C

External finish color

RAL 5015

Rubber membrane **EPDM**

Counter flange galvanized



Warranty months

24

Model	Capacity	Height	Diameter	Length	Maximum working pressure	Standard precharge pressure	Packing	Connection
	<i>(liter)</i>	<i>H (mm)</i>	<i>Ø (mm)</i>	<i>L (mm)</i>	<i>(bar)</i>	<i>(bar)</i>	<i>(mm)</i>	<i>(inch)</i>
VA024	24	305	280	485	10	4	(Pz1) 510X290X320	1 "
VA050	50	380	365	585	10	4	(Pz1) 380X400X590	1 "

SERIES VA-VAV

VA



VAV



Pressure tank with replaceable membrane for pressurized systems of sanitary water.

Working temperature
- 10° C
+ 100° C

External finish color

RAL 5015

Rubber membrane **EPDM**

outer flange galvanized



Warranty months

24

Model	Capacity	Height	Diameter	Length	Maximum working pressure	Standard precharge pressure	Packing	Connection
	(liter)	H (mm)	Ø (mm)	L (mm)	(bar)	(bar)	(mm)	(inch)
VA8	8	315	200	-	10	4	(Pz1) 220X220X335	¾ "
VA18	18	430	280	-	10	4	(Pz1) 290X290X450	¾ "
VA24	24	483	280	-	10	4	(Pz1) 290X290X510	1 "
VA35	35	440	365	-	10	4	(Pz1) 380X400X460	1 "
VAV50	50	720	365	-	10	4	(Pz1) 380X380X730	1 "
VAV60	60	808	365	-	10	4	(Pz1) 380X390X820	1 "
VAV80	80	856	415	-	10	4	(Pz1) 420X430X850	1 "
VAV100	100	855	495	-	10	4	(Pz1) 510X520X870	1 "
VAV200	200	1085	600	-	10	4	(Pz1) 610X620X1111	1 ¼ "
VAV300	300	1240	650	-	10	4	(Pz1) 670X680X1290	1 ¼ "
VAV500	500	1490	750	-	10	4	(Pz1) 750X770X1510	1 ¼ "

SERIES VAV

VAV



Pressure tank with replaceable membrane for pressurized systems of sanitary water.

Working temperature

- 10° C
+ 100° C

External finish color

RAL 3000

Rubber membrane

EPDM

Painted counter flange



Warranty months

24

Model	Capacity	Height	Diameter	Length	Maximum working pressure	Standard precharge pressure	Packing	Connection
	<i>(liter)</i>	<i>H (mm)</i>	<i>Ø (mm)</i>	<i>L (mm)</i>	<i>(bar)</i>	<i>(bar)</i>	<i>(mm)</i>	<i>(inch)</i>
VAV750	750	1900	750	-	10	4	(Pz1) 750X750X2030	2 "
VAV1000	1000	2180	800	-	10	4	(Pz1) 800X800X2330	2 "

SERIES VB-VBV 16 bar

VB



VBV



High pressure tank with replaceable membrane for pressurized systems of sanitary water.

Working temperature
- 10° C
+ 100° C

External finish color

RAL 5015

Rubber membrane **EPDM**

Counter flange galvanized



Warranty months

24

Model	Capacity	Height	Diameter	Length	Maximum working pressure	Standard precharge pressure	Packing	Connection
	(liter)	H (mm)	Ø (mm)	L (mm)	(bar)	(bar)	(mm)	(inch)
VB8	8	310	200	-	16	8	(Pz1) 220X225X335	¾ "
VB24	24	483	270	-	16	8	(Pz1) 290X290X510	1 "
VBV100	100	849	495	-	16	8	(Pz1) 510X520X850	1 "
VBV200	200	1085	600	-	16	8	(Pz1) 610X620X1111	1 ¼ "
VBV300	300	1240	650	-	16	8	(Pz1) 670X680X1290	1 ¼ "
VBV500	500	1490	750	-	16	8	(Pz1) 750X770X1510	1 ¼ "

SERIES AX



Pressure tank with replaceable membrane for pressurized systems of sanitary water.

Working temperature

- 10° C
+ 100° C

STAINLESS STEEL

Rubber membrane **EPDM**

Stainless steel AISI 304 counter flange



Warranty months

24

Model	Capacity	Height	Diameter	Length	Maximum working pressure	Standard precharge pressure	Packing	Connection
	(liter)	H (mm)	Ø (mm)	L (mm)	(bar)	(bar)	(mm)	(inch)
AX24	24	510	270	-	10	4	(Pz1) 290X290X510	1 "

위생안전기준 인증서

- 1. 인 증 번 호 : KCW-2022-0143
- 2. 제조 업체명 : ZILIO INDUSTRIES S.p.A
- 3. 대 표 자 : Simone Zilio
- 4. 본 사 주 소 : Via Sega Vecchia, 65 - Friola di Pozzoleone (VI) - ITALY
- 5. 공장 소재지 : Via Sega Vecchia, 65 - Friola di Pozzoleone (VI) - ITALY
- 6. 제 품 명 : 압력탱크
- 7. 종류, 등급 또는 호칭 : 별지 참조
- 8. 용 도 : 급수설비

「수도법」 제14조제1항 및 「수도용 자재와 제품의 위생안전기준 인증 등에 관한 규칙」 제8조제1항에 따라 인증서를 발급한 제품입니다.

2022년 08월 19일



한국물기술인증원

